# MAMELUCO S110





# Descripción:

Nuestra línea de buzos descartables STEELPRO brinda a los usuarios protección contra polvo y partículas líquidas, además de agentes no químicos que puedan ingresar al cuerpo.

El Buzo S110 es un traje básico de protección descartable para trabajos livianos, protegiendo la integridad del trabajador, brindando transpirabilidad y comodidad.

# Características:

- Confeccionado en tela no tejida de 50 gramos, compuesta de 3 capas.
- Primera capa de 100% Polietileno, película respirable de 20 gramos.
- Segunda capa de recubrimiento termo fusible adhesiva de 2 gramos.
- Tercera capa de 100% Polipropileno de 28 gramos. 58% Polipropileno 42% Polietileno
- Tecnología con tratamiento laminado respirable, que permite la evaporación de la transpiración y presenta buen comportamiento como regulador de la temperatura corporal.
- Tela laminada microporosa SF50 de 50 g/m2

# **Recomendaciones:**

- EN ISO 13934-1:2013
- EN ISO 13935-2:2014
- ASTM E96/E96M-2016
- ISO 9073-2:1995
- ISO 9073-1:1989
- AATCC TM 35-2018



Ni el vendedor ni el fabricante serán responsables de cualquier lesión personal, pérdida o daños ya sean directos o consecuentes del mal uso de este producto. Antes de ser usado, se debe determinar si el producto es apropiado para el uso pretendido.







Page 1 of 7



Test Report No. PPE 205227(1)/15

XIANTAO KIMBERLY PROTECTIVE PRODUCTS CO LTD GROUP 2 BAGUANG VILLAGE. PENGCHANG TOWN XIANTAO CITY HURFI CHINA



The following sample was submitted and identified by the client as:

Sample of white micro-porous coverall, in sizes, M, L, XL, XXL, 3XL & 4XL. Sample Description:

Date Sample(s) Received: 03<sup>rd</sup> June 2015

Testing Period: Tested between 08/06/2015 and 01/07/2015

Test(s) Requested: EN 14325:2004 as detailed in appendix A

EN 1149-1: 2006 Protective clothing - Electrostatic properties

Date: 2 July 2015

Part 1: Measurement of Surface Resistivity

EN 13034:2005 Resistance to penetration by liquids in the form of a light

EN ISO 13982-2:2004 Determination of inward leakage of aerosols of fine

particles into suits.

Detailed in Appendix A Test Results:

Signed for and on behalf of SGS United Kingdom Ltd

Chris Walker B.Sc. (Hons) Technical Manager

This document is issued by the Company subject to its General Conditions of Service, available on request or accessible at <a href="https://www.sgs.com/terms.org/conditions.htm">www.sgs.com/terms.org/conditions.htm</a>
and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sgs.com/terms.org/commans.or cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or faisification of the content or appearance of this document is unlewful and offenders may be prosecuted to the fullest extent of the law."

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. This document cannot be reproduced except in full, without prior approval of the Company

Tests denoted with an \* have been subcontracted to another UKAS Approved Laboratory. Tests marked (Non-UKAS Accredited) in this report/certificate are not included in the UKAS Accredited Schedule for our laboratory.

Opinions and interpretations expressed herein are outside the scope of UKAS Accreditation.

SGS United Kingdom Ltd

Units 41 & 43, The Listerhills Park of Science and Commerce, Campus Road, Bradford BD7 1HR Tel +44 (0)1274 303080 Fax +44 (0)1274 303098

Registered in England No. 1193985 Rossmore Business Park, Ellesmere Port, Cheshire CH65 3EN www.sgs.com

Member of SGS Group (SA Group)



Siguenos: **#**@0**@** @importadoraconsuelo



Page 2 of 7

PPE 205227(1)/15

### Appendix A: Test Results

# BS EN 14325:2004 Protective clothing against chemicals

Test Methods and performance classification of chemical protective clothing materials, seams, joins and assemblages.

Section 4: Performance classification of materials.

Sample for testing in accordance with EN 14325:2004 were conditioned in standard atmosphere 23±2°C and 50% ±4% Relative Humidity for at least 24 hours prior to testing.

Claus	9	Test Method	Result	Class	Comments
4.2	Pre-conditioning (5 cycles of cleaning)	Not Applicable Limited Use	-		-
4.4	Abrasion Resistance	EN 530 Method 2	>10 Cycles (Visual assessment)	1	>10 but <100
4.5	Flex cracking resistance	ISO 7854 Method B	3 40,000 Cycles (Visual assessment)	5	>15,000 but <40,000
4.7	Trapezoidal tear resistance	ISO 9073-4	XD = 31.2 N MD= 52.9 N	2	
4.9	Tensile Strength	ISO 13934-1	XD = 42.1 N MD= 65.7 N	1	
4.10	Puncture Resistance	EN863	6.67 N	1	
4.12	Repellency to	EN ISO 6530:2005			
	liquids*	30% H <sub>2</sub> SO <sub>4</sub>	97.5%	3	]
		10% NaOH	97.5%	3	
		o-Xylene	96.4%	3	]
		Butan-1-ol	97.7%	3	
4.13	Resistance to	EN ISO 6530:2005			
	penetration by	30% H <sub>2</sub> SO <sub>4</sub>	0.0%	3	]
	liquids*	10% NaOH	0.0%	3	]
		o-Xylene	0.0%	3	]
		Butan-1-ol	0.0%	3	<u> </u>

Section 5: Performance requirements for seams joins and assemblages

Claus	e	Test Method	Result	Class	Comments
5.2	Pre-conditioning	Not applicable	-	-	
	(5 cycles of cleaning)	Limited Use			
5.5	Seam Strength	ISO 13935-2	Waist seam = 73.7N Leg seam = 65.1N Arm seam = 77.7N Hood seam = 63.1N	2	Fabric tears

An estimation of uncertainty of measurement has not been taken into account when making a judgement on any passifall

This document is issued by the Company subject to its General Conditions of Service, available on request or accessible at <a href="https://www.ags.com/ferms\_end\_conditions.htm">www.ags.com/ferms\_end\_conditions.htm</a>
and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.ags.com/ferms\_end-coursent.htm">www.ags.com/ferms\_end-coursent.htm</a>.

Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's Indiana at the time of its intervention only and within the limits of Clients instructions, if any. The Company's sole responsibility is to its Client and this document does not accessed parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized attention, forgery or faisification of the content or appearance of this document is unleavful and offenders may be prosecuted to the fullest extent of the law."

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. This document cannot be reproduced except in full, without prior approval of the Company.

Tests denoted with an \* have been subcontracted to another UKAS Approved Laboratory. Tests marked (Non-UKAS Accredited) in this report/certificate are not included in the UKAS Accredited Schedule for our laboratory.

Opinions and interpretations expressed herein are outside the scope of UKAS Accreditation.

SGS United Kingdom Ltd

Units 41 & 43, The Listerhills Park of Science and Commerce, Campus Road, Bradford BD7 1HR Tel +44 (0)1274 303080 Fax +44 (0)1274 303098

Registered in England No. 1193985 Rossmore Business Park, Ellesmere Port, Cheshire CH65 3EN www.sgs.com

Member of SGS Group (SA Group)



Siguenos: **#**@0**@** @importadoraconsuelo



Page 3 of 7

PPE 205227(1)/15

# EN 1149-1:2006 Protective clothing – Electrostatic properties

# Part 1: Measurement of Surface Resistivity\*

The sample was conditioned and tested at 23 ± 1 °C and 25 ± 5 % Relative Humidity

The surface resistivity of the test sample was determined according to the method specified in BS EN 1149-1:2008.

						Mean
Surface Resistance (Ω)	>2.00 x 10 <sup>10</sup>					
Surface Resistivity (Ω)	>3.96 x 10"	>3.96 x 1011				

### Note

As the sample is intended for single use, it did not require washing prior to testing.

For a material containing conductive threads in a stripe or grid pattern the spacing of the conductive threads in one direction shall not exceed 10mm.

The maximum acceptable resistance specified in EN 1149-5:2008 is  $\leq 2.5 \times 10^{9} \Omega$  measured on at least one surface. The tested sample fails to meets this requirement.

EN13034:2005 Protective clothing against liquid chemicals – Performance requirements for chemical protective clothing offering limited protective performance against liquid chemicals (Type 6 and Type PB [6] equipment)

Clause 5.2 Resistance to penetration by liquids in the form of a light spray (mist test)\*

Test Method: The test method used was the total inward leakage method defined in ISO 17491-4

The standard calls for the testing to be carried out using three suits.

The physical dimensions of wearer(s) are shown below;

Wearer	Height (cm)	Chest (cm)	Suit Size
JA	182	98	XL

Undergarments as detailed in ISO 17491-4 and a "Sontara" absorbent suit were worn directly under the test

garment.

The device is a white material hooded one piece coverall incorporating elasticated ankles, waist, hood and cuffs.

The device is a white material hooded one piece coverall incorporating elasticated ankles, waist, hood and cuffs. There is a double action zip at the front of the suit which runs from crotch to the neck and is covered during use by a flap which is sealed onto the suit material by means of double sided tape.

At the request of the client the coveralls were taped onto a scott "promask" full face mask, wellington boots and rubber gloves.

The wearers were dressed in accordance with the manufacturer's dressing procedures.

This document is issued by the Company subject to its General Conditions of Service, available on request or accessible at <a href="www.sgs.com/terms\_end\_conditions.htm">www.sgs.com/terms\_end\_conditions.htm</a>
and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>
Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not expenses to a transaction from exercising all their right's and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlewful and offenders may be prosecuted to the fullest extent of the law."

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. This document cannot be reproduced except in full, without prior approval of the Company

Tests denoted with an \* have been subcontracted to another UKAS Approved Laboratory. Tests marked (Non-UKAS Accredited) in this report/certificate are not included in the UKAS Accredited Schedule for our laboratory.

Opinions and interpretations expressed herein are outside the scope of UKAS Accreditation

SGS United Kingdom Ltd

Units 41 & 43, The Listerhills Park of Science and Commerce, Campus Road, Bradford BD7 1HR Tel +44 (0)1274 303080 Fax +44 (0)1274 303098

Registered in England No. 1193985 Rossmore Business Park, Ellesmere Port, Cheshire CH65 3EN www.sgs.com

Member of SGS Group (SA Group)







Page 4 of 7

PPE 205227(1)/15

### Test Results:

In response to the question "does the suit fit", the test subject answered "Yes".

After testing in accordance with the practical movements defined in EN13034 for type 6 clothing no damage was observed on the suit.

Surface tension measurements of the test solution were recorded in the reservoir and at the nozzle before and after testing and these ranged from 46.6 to 47.3Nm<sup>-1</sup>x10<sup>-3</sup> and 44.9 to 46.6Nm<sup>-1</sup> x10<sup>-3</sup> respectively.

A temperature measurement of 24.2°C was recorded in the test chamber immediately after testing.

Leakage stains were detected on the back, the front of the left leg and the right arm of the first dosimeter tested.

As the observed leakage areas were clearly in excess of three times the area of the calibrated stain, no further testing was carried out.

## Assessment of Compliance

EN 130345 for type 6 clothing states that:

"All suits shall pass the test, i.e. the total area on any one undergamment of each suit shall be less than or equal to three times the total calibrated stain area".

For this suit as stains were detected, the sample therefore fails to comply with the requirements of EN13034 for type 6 clothing.

EN ISO 13982-1:2004 Protective clothing for use against solid particulates – Part 1: Performance requirements for chemical protective clothing providing protection to the full body against airborne solid particulates (type 5 clothing)\*

EN ISO 13982:2004 Part 2 - Determination of inward leakage of aerosols of fine particles into suits
Test Methods: The test method used was the total inward leakage method defined in BS EN ISO 13982-2: 2004.

The physical dimensions of the wearers are shown below:

Wearer	Height (cm)	Chest (cm)	Suit Size
DB	178	96	L
JB	164	100	L
KWS	180	96	XL
LF	168	105	L
TW	177	105	XL

All wearers were close fitting polyester/cotton long trousers and long sleeve T-shirts. The 2L/min air sample from the suit was replaced with clean air.

This document is issued by the Company subject to its General Conditions of Service, available on request or accessible at <a href="https://www.ags.com/terms\_end\_conditions.htm">www.ags.com/terms\_end\_conditions.htm</a>
and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.ags.com/terms\_end-com/terms\_

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. This document cannot be reproduced except in full, without prior approval of the Company.

Tests denoted with an \* have been subconfracted to another UKAS Approved Laboratory. Tests marked (Non-UKAS Accredited) in this report/certificate are not included in the UKAS Accredited Schedule for our laboratory.

Opinions and interpretations expressed herein are outside the scope of UKAS Accreditation.

SGS United Kingdom Ltd

Units 41 & 43, The Listerhills Park of Science and Commerce, Campus Road, Bradford BD7 1HR Tel +44 (0)1274 303080 Fax +44 (0)1274 303098

Registered in England No. 1193985 Rossmore Business Park, Ellesmere Port, Cheshire CH65 3EN www.sgs.com

Member of SGS Group (SA Group)



Siguenos:

(f) (a) (b) (c)

(a) (a) (c) (c) (c)

(b) (c) (c) (c) (c)

(c) (c) (c) (c) (c)

(d) (c) (c) (c)

(e) (c) (c)

(e) (c) (c) (c)

(e)



Page 5 of 7

PPE 205227(1)/15

The device is a white material one piece hooded coverall incorporating elasticated ankles, waist, hood and wrists. There is a double action zip at the front of the suit which runs from the crotch to the neck and is covered during use by a flap which is sealed onto the suit material by means of double sided tape.

The wearer was dressed in accordance with the manufacturer's instructions. At the request of the client the coveralls were worn with nitrile disposable gloves, wellington boots and Scott "Promask" full face mask.

#### Test results:

In response to the question "does the suit fit", all test subjects answered "Yes".

After testing in accordance with the movements defined in clause 4.3.2 of BS EN ISO 13982-1: 2004, no damage to the suit was observed.

Temperature and relative humidity measurements were recorded in the test chamber before and after each test and these ranged from 24.5 to 27.4°C and 47.1 to 59.6%, respectively.

Inward leakage results in terms of concentration of salt inside the suit as a percentage of the challenge concentration are shown in the following tables:

Table 1: NaCl inward leakage (%) individual results

Wearer	Position	Knee	Waist	Breast	Average
DB	Stand	2.247	2.156	2.881	2.428
	Walk	0.651	2.004	2.676	1.777
	Squat	3.253	8.774	2.384	4.804
	Average	2.050	4.311	2.647	3.003

Wearer	Position	Knee	Waist	Breast	Average
DB	Stand	1.084	1.411	1.903	1.466
	Walk	0.349	0.841	0.868	0.686
	Squat	1.684	4.137	3.156	2.992
	Average	1.039	2.129	1.976	1.715

Wearer	Position	Knee	Waist	Breast	Average
JB	Stand	0.314	1.645	2.242	1.401
	Walk	0.287	0.663	0.656	0.536
	Squat	1.964	11.733	8.183	7.293
	Average	0.855	4.681	3.694	3.077

Wearer	Position	Knee	Waist	Breast	Average
JB	Stand	0.895	3.001	2.276	2.057
	Walk	0.836	8.132	4.958	4.642
	Squat	0.529	6.422	6.138	4.363
	Average	0.753	5.852	4.457	3.688

This document is issued by the Company subject to its General Conditions of Service, available on request or accessible at <a href="https://www.sgs.com/terms\_end\_conditions.htm">www.sgs.com/terms\_end\_conditions.htm</a>, and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sgs.com/terms\_e-document.htm">www.sgs.com/terms\_e-document.htm</a>.

Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not expensive parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized attention, forgery or faisification of the content or appearance of this document is unlewful and offenders may be prosecuted to the fullest extent of the law."

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. This document cannot be reproduced except in full, without prior approval of the Company.

Tests denoted with an \* have been subcontracted to another UKAS Approved Laboratory. Tests marked (Non-UKAS Accredited) in this report/certificate are not included in the UKAS Accredited Schedule for our laboratory.

sed herein are outside the scope of UKAS Accreditation.

SGS United Kingdom Ltd

Units 41 & 43, The Listerhills Park of Science and Commerce, Campus Road, Bradford BD7 1HR Tel +44 (0)1274 303080 Fax +44 (0)1274 303098

Registered in England No. 1193985. Rossmore Business Park, Ellesmere Port, Cheshire CH65.3EN. www.sgs.com

Member of SGS Group (SA Group)







Mozene

Page 6 of 7

White

PPE 205227(1)/15

Nearer	Position	Knee	Waist	Breast	Average
(WS	Stand	0.006	0.018	0.097	0.040
	Walk	0.342	0.437	0.931	0.570
	Squat	1.512	2.770	4.661	2.981
	Average	0.620	1.075	1.896	1.917
	1				
Wearer	Position	Knee	Waist	Breast	Average
KWS	Stand	0.111	0.348	0.535	0.332
	Walk	0.467	1.067	1.642	1.059
	Squat	2.574	25.514	6.749	11.612
	Average	1.051	8.976	2.975	4.334
Wearer	Position	Knee	Waist	Breast	Average
LF	Stand	0.005	0.05	0.043	0.017
	Walk	0.448	0.391	0.488	0.442
	Squat	0.875	4.153	4.330	3.113
	Average	0.442	1.510	1.620	1.191
Wearer	Position	Knee	Waist	Breast	Average
LF	Stand	0.124	0.114	0.082	0.107
	Walk	0.480	0.412	0.491	0.461
	Squat	0.769	2.058	3.081	1.970
	Average	0.458	0.861	1.218	0.846
	1				
Wearer	Position	Knee	Waist	Breast	Average
TW	Stand	0.876	0.499	0.607	0.660
	Walk	2.095	3.506	2.915	2.839
	Squat	16.684	8.744	8.885	11.438
	Average	6.551	4.250	4.135	4.979
Wearer	Position	Knee	Waist	Breast	Average
TW	Stand	0.048	0.132	0.221	0.134
	Walk	0.640	1.085	0.898	0.134
	Squat	1.264	4.987	12.243	6.158
	Average	0.651	2.082	4.454	2.389
	Avelage	0.001	2.002	7.707	2.308
Table 2: Total in	ward leakage (%) (Over	all average, all we	arers)		
Position	Knee	Wa		Breast	Average

This document is issued by the Company subject to its General Conditions of Service, available on request or accessible at <a href="https://www.sgs.com/ferms\_end\_conditions.htm">www.sgs.com/ferms\_end\_conditions.htm</a>
and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sgs.com/ferms\_end-coument.htm">www.sgs.com/ferms\_end-coument.htm</a>.

Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is edvised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exponent parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized attention, forgery or falsification of the content or appearance of this document is unleavful and offenders may be prosecuted to the fullest extent of the law."

0.933

1.854

7.926

3.571

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. This document cannot be reproduced except in full, without prior approval of the Company.

Tests denoted with an \* have been subcontracted to another UKAS Approved Laboratory. Tests marked (Non-UKAS Accredited) in this report/certificate are not included in the UKAS Accredited Schedule for our laboratory.

Opinions and interpretations expressed herein are outside the scope of UKAS Accreditation.

0.571

0.660

3.111

1.447

SGS United Kingdom Ltd

Stand

Squat

Average

Walk

Units 41 & 43, The Listerhills Park of Science and Commerce, Campus Road, Bradford BD7 1HR Tel +44 (0)1274 303080 Fax +44 (0)1274 303098

Registered in England No. 1193985 Rossmore Business Park, Ellesmere Port, Cheshire CH65 3EN www.sgs.com

Member of SGS Group (SA Group)



RAZON SOCIAL: IMPORTADORA CONSUELO E.I.R.L. R.U.C.: 20611465786

1.089

1.652

5.981

2.907

0.864

1.389

5.672

2.642



Page 7 of 7

PPE 205227(1)/15

Table 3: Total inward leakage per test subject

Wearer	Average
DB	2.359
JB	3.382
KWS	2.766
LF	1.018
TW	3.684
Average	2.642

# Assessment of compliance:

BS EN ISO 13982-1 specifies the requirements and classes of type 5 suits as:

When tested in accordance with BS EN ISO 13982-2 the type 5 protective clothing shall be characterized by the following parameters:

IL 82/90: the inward leakage value (in percent), equal to or superior to 82/90 (91.1%) of all IL values measured (all exercises, all sampling positions, all suits);

TILS8/10: the "total inward leakage per suit" value, equal or superior to 80% of all TILS-values.

Type 5 chemical protective clothing shall meet at least the following requirements: IL 8290 <30% and TILS 810-15%

For this suit, all of the IL results are less than 30% and all of the TILS are less than 15%.

The sample complies with the requirements of BS EN ISO 13982-1 (2004) for inward leakage of aerosol of solid

\*\*\* End of Report\*\*\*



This document is issued by the Company subject to its General Conditions of Service, available on request or accessible at <a href="www.sgs.com/terms\_end\_conditions.htm">www.sgs.com/terms\_end\_conditions.htm</a>
and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="www.sgs.com/terms\_end-document.htm">www.sgs.com/terms\_end-document.htm</a>.

Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is edvised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exponente parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized attention, forgery or faisification of the content or appearance of this document is unleaded attention.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. This document cannot be reproduced except in full, without prior approval of the Company.

Tests denoted with an \* have been subcontracted to another UKAS Approved Laboratory. Tests marked (Non-UKAS Accredited) in this report/certificate are not included in the UKAS Accredited Schedule for our laboratory.

Opinions and interpretations expressed herein are outside the scope of UKAS Accreditation.

SGS United Kingdom Ltd

Units 41 & 43, The Listerhilis Park of Science and Commerce, Campus Road, Bradford BD7 1HR Tel +44 (0)1274 303080 Fax +44 (0)1274 303098

Registered in England No. 1193985 Rossmore Business Park, Ellesmere Port, Cheshire CH65 3EN www.sgs.com

Member of SGS Group (SA Group)



Siguenos:

(f) (a) (b) (d)

(a) (a) (d) (d)

(b) (d) (d)

(c) (d) (d)

(d) (d) (d)

(e) (d) (d)